

| SIZE | Neck Velocity (fpm) | | 250 | | 500 | | 750 | | 1000 | | 1250 | | 1500 | |
|------|-----------------------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|--------|-------|-------|-------|
| | Velocity Pressure (in.,wg) | | 0.004 | | 0.016 | | 0.035 | | 0.062 | | 0.097 | | 0.140 | |
| | Total Pressure | | 0.023 | 0.029 | 0.076 | 0.096 | 0.165 | 0.200 | 0.247 | 0.292 | 0.387 | 0.417 | 0.540 | 0.570 |
| | Deflection | | 0 | 22.5 | 0 | 22.5 | 0 | 22.5 | 0 | 22.5 | 0 | 22.5 | 0 | 22.5 |
| 6 | Neck Area sq.ft 0.196 | CFM | 50 | | 100 | | 150 | | 200 | | 250 | | 300 | |
| | | NC | - | - | - | - | - | 20 | 24 | 34 | 32 | 40 | 37 | 43 |
| | | Throw (ft.) | 10 | 9 | 13 | 12 | 17 | 15 | 19 | 17 | 22 | 19 | 24 | 22 |
| 8 | Neck Area sq.ft 0.349 | CFM | 90 | | 180 | | 270 | | 350 | | 33 440 | | 530 | |
| | | NC | - | - | - | 18 | 22 | 26 | 25 | 32 | | 40 | | |
| | | Throw (ft.) | 13 | 12 | 18 | 17 | 22 | 20 | 25 | 23 | 27 | 25 | 31 | 28 |
| 10 | Neck Area sq.ft 0.545 | CFM | 140 | | 280 | | 410 | | 550 | | 690 | | 820 | |
| | | NC | - | - | - | 15 | 15 | 21 | 20 | 26 | 26 | 33 | | |
| | | Throw (ft.) | 16 | 14 | 23 | 20 | 28 | 25 | 31 | 28 | 36 | 32 | 36 | 33 |
| 12 | Neck Area sq.ft 0.785 | CFM | 200 | | 400 | | 590 | | 790 | | 990 | | 1180 | |
| | | NC | - | - | - | - | 16 | 22 | 22 | 32 | 31 | 38 | 35 | 48 |
| | | Throw (ft.) | 19 | 17 | 27 | 24 | 32 | 30 | 38 | 34 | 41 | 39 | 43 | 41 |
| 14 | Neck Area sq.ft 1.069 | CFM | 270 | | 540 | | 810 | | 1070 | | 1340 | | 1610 | |
| | | NC | - | - | - | - | 16 | 29 | 24 | 32 | 29 | 34 | 37 | 45 |
| | | Throw (ft.) | 22 | 21 | 32 | 28 | 38 | 35 | 44 | 40 | 49 | 44 | 54 | 47 |
| 16 | Neck Area sq.ft 1.396 | CFM | 350 | | 700 | | 1050 | | 1400 | | 1750 | | 2100 | |
| | | NC | - | - | - | - | 19 | 27 | 29 | 34 | 32 | 41 | 37 | 45 |
| | | Throw (ft.) | 25 | 23 | 36 | 31 | 43 | 39 | 51 | 45 | 56 | 52 | 63 | 55 |
| 20 | Neck Area sq.ft 2.182 | CFM | 550 | | 1100 | | 1640 | | 2190 | | 2730 | | 3280 | |
| | | NC | - | - | - | - | 19 | 27 | 30 | 34 | 32 | 40 | 38 | 47 |
| | | Throw (ft.) | 31 | 27 | 44 | 41 | 54 | 49 | 63 | 57 | 70 | 64 | 74 | 71 |
| 24 | Neck Area sq.ft 3.142 | CFM | 790 | | 1580 | | 2360 | | 3150 | | 3930 | | 4720 | |
| | | NC | - | - | - | - | 20 | 26 | 30 | 34 | 33 | 41 | 39 | 48 |
| | | Throw (ft.) | 33 | 28 | 54 | 49 | 65 | 58 | 74 | 68 | 83 | 78 | 92 | 84 |

THE THROW VALUES ARE BASED ON A 50 FPM TERMINAL VELOCITY.
 DASHED LINE IN NC BOX INDICATES NOISE LEVEL IS LESS THAN 15.
 NC LEVEL IS BASED ON 10dB ROOM ATTENUATION(PWL RE:10-12 WATTS) WITH ONE DIFFUSER OPERATING.

**Seiho International reserves the right to make changes without prior notice.

*This performance data is proprietary to Seiho International, Inc., and shall not be used except as expressly authorized by the Company.