

SIZE	Nozzle Area	Nozzle Velocity (m/s)	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0
PK8K	Ø76 0.0045sq.m	CMH	45	70	95	120	145	170	195	220	245
		Pa	2.5	5.5	10.0	16.0	24.5	33.5	44.0	56.0	69.5
		Throw (Vt=@0.5/s)	1.5	2.3	3.0	3.8	4.6	5.4	6.2	7.0	7.8
		Throw (Vt=@0.25/s)	2.4	3.7	4.8	6.1	7.4	8.7	10.0	11.2	12.5
		NC	-	-	-	-	21.2	27.5	32.7	37.1	40.8
PK10K	Ø115 0.0104sq.m	CMH	100	150	200	250	300	350	400	450	500
		Pa	2.4	5.6	10.0	15.6	22.4	30.4	40.4	51.2	62.5
		Throw (Vt=@0.5/s)	2.2	3.3	4.5	5.6	6.8	8.0	9.3	10.5	11.8
		Throw (Vt=@0.25/s)	3.5	5.3	7.2	9.0	10.9	12.8	14.5	16.8	18.9
		NC	-	-	-	-	19.3	25.0	30.3	34.4	37.9
PK12K	Ø135 0.0143sq.m	CMH	130	200	270	340	410	480	550	620	690
		Pa	2.4	5.6	10.0	16.0	23.2	31.6	41.6	53.2	65.7
		Throw (Vt=@0.5/s)	2.6	3.9	5.2	6.6	7.9	9.4	10.9	12.2	13.7
		Throw (Vt=@0.25/s)	4.2	6.2	8.3	10.6	12.6	15.0	17.4	19.5	21.9
		NC	-	-	-	-	19.5	24.9	30.2	34.3	38.1
PK12WK	Ø155 0.0189sq.m	CMH	170	260	350	440	530	620	710	800	890
		Pa	2.4	5.6	10.0	16.0	23.2	31.6	41.2	52.0	63.7
		Throw (Vt=@0.5/s)	3.0	4.6	6.1	7.6	9.2	10.9	12.5	14.0	15.6
		Throw (Vt=@0.25/s)	4.8	7.4	9.8	12.2	14.7	17.4	20.0	22.4	25.0
		NC	-	-	-	-	21.3	27.4	32.3	36.0	39.1
PK16K	Ø186 0.0272sq.m	CMH	260	400	540	680	820	960	1100	1240	1380
		Pa	2.0	5.0	8.5	13.5	20.5	27.5	35.5	44.5	55.0
		Throw (Vt=@0.5/s)	3.4	5.2	6.8	8.5	10.2	12.1	13.9	15.6	17.2
		Throw (Vt=@0.25/s)	5.5	8.4	10.9	13.6	16.4	19.4	22.3	25.0	27.6
		NC	-	-	-	18.2	25.4	31.6	36.1	39.9	43.4
PK20K	Ø245 0.0471sq.m	CMH	430	655	880	1105	1330	1555	1780	2005	2230
		Pa	2.1	4.9	8.6	13.4	19.0	26.5	34.5	43.5	53.5
		Throw (Vt=@0.5/s)	4.0	6.1	8.1	10.1	12.1	14.2	16.2	18.2	20.2
		Throw (Vt=@0.25/s)	6.4	9.8	13.0	16.2	19.4	22.7	25.9	29.1	32.3
		NC	-	-	-	18.7	25.8	32.0	36.5	40.4	43.9

DASHED LINE IN NC BOX INDICATES NOISE LEVEL IS LESS THAN 17.
 NC LEVEL IS BASED ON 10dB ROOM ATTENUATION(PWL RE:10-12 WATTS) WITH ONE DIFFUSER OPERATING.

*Seiho International reserves the right to make changes without prior notice.
 *This performance data is proprietary to Seiho International, Inc., and shall not be used except as expressly authorized by the Company.