

外壁用ステンレス製換気口〈フラットグリル〉

CX-S 〈ガラリ型〉





材質 SUS304

仕上 シルバー焼付塗装

金網付型式

CX-SN 10M
CX-SN 5M
CX-SN 3M




Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
CX65S	62	112	10	42	¥2,200	¥500	¥1,400
CX75S	72	112	10	42	¥2,200	¥500	¥1,400
CX100S	97	135	10	47	¥2,500	¥600	¥1,500
CX125S	122	159	10	52	¥3,200	¥700	¥1,800
CX150S	147	183	10	52	¥3,300	¥1,200	¥1,900
CX175S	170	209	10	67	¥5,300	¥1,700	¥2,100
CX200S	197	234	10	77	¥5,600	¥2,100	¥2,400

圧力損失特性

サイズ	圧力損失係数	流量係数	有効開口
	排気	開口率	面積 (cm ²)
100	2.27	66.4%	52.1
125	1.67	77.4%	94.9
150	3.19	56.0%	98.9
175	1.71	76.5%	184
200	3.15	56.3%	176.9



CXD-S 〈ガラリ型 防火ダンパー付〉





材質 フェイス: SUS304
FD: 鋼板 1.6t

仕上 シルバー焼付塗装

温度フェース 標準72℃
オプション120℃・180℃

金網付型式

CXD-SN 10M
CXD-SN 5M
CXD-SN 3M




Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
CXD100S	97	135	10	47	¥5,800	¥600	¥1,500
CXD125S	122	159	10	52	¥8,400	¥700	¥1,800
CXD150S	146	183	10	47	¥8,500	¥1,200	¥1,900
CXD200S	197	234	10	62	¥12,000	¥2,100	¥2,400

圧力損失特性

サイズ	圧力損失係数	流量係数	有効開口
	排気	開口率	面積 (cm ²)
100	2.8	59.8%	46.9
125	2.2	67.4%	82.7
150	3.51	53.4%	94.3
200	3.33	54.8%	172.2



CXD-SC 〈ガラリ型 防火ダンパー付〉



材質 フェイス: SUS304
FD: SUS304 1.5t



仕上 シルバー焼付塗装

フェイス着脱式

温度フェース 標準72℃
オプション120℃・180℃

金網付型式

CXD-SCN 10M
CXD-SCN 5M
CXD-SCN 3M



Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
CXD75SC	72	112	10	52	¥5,000	¥500	¥1,400
CXD100SC	97	135	10	67	¥5,300	¥600	¥1,500
CXD125SC	122	159	10	83	¥7,000	¥700	¥1,800
CXD150SC	147	183	10	97	¥7,500	¥1,200	¥1,900
CXD175SC	172	209	10	107	¥10,500	¥1,700	¥2,100
CXD200SC	197	234	10	117	¥11,800	¥2,100	¥2,400

圧力損失特性

サイズ	圧力損失係数	流量係数	有効開口
	排気	開口率	面積 (cm ²)
100	3.37	54.5%	42.8
125	2.41	64.4%	78.9
150	3.69	52.1%	92
175	2.02	70.4%	169.3
200	3.53	53.2%	167.1

